

Watkins Wellness®

# INSTALLATION

Of your **SpaGlo® CONTROLLER EAGLE RETROFIT**



## TABLE OF CONTENTS

INSTALLATION REQUIREMENTS.....	1
TOOLS REQUIRED	
ADDITIONAL PARTS REQUIRED	
MODULE/CONTROLLER OVERVIEW.....	2
REMOVING SPAGLO MODULE .....	3
SPAGLO MODULE REMOVAL	
SPAGLO EAGLE RETROFIT CONTROLLER INSTALLATION .....	4
SPAGLO EAGLE RETRO INSTALLATION	

**INTENDED USE IN KIT # 78864**

# INSTALLATION REQUIREMENTS

## TOOLS REQUIRED

Cordless Drill



Phillips Screwdriver



Flat Head Screw driver



Wire Cutter



Zip-Ties



Large Channel Lock and Needle-nose Pliers



Safety Glasses



Masking Tape-Marker



## PARTS REQUIRED

X2



**SpaGlo® CONTROLLER EAGLE RETROFIT  
(PN 78864)**


## IMPORTANT INFORMATION




**IMPORTANT**

This SpaGlo controller will work for Eagle boxes inside the Caldera Spas.














# MODULE/CONTROLLER OVERVIEW



SpaGlo<sup>®</sup>  
MODULE  
(FACTORY  
INSTALLED)



SpaGlo<sup>®</sup> CONTROLLER EAGLE RETROFIT

 J13	 J12	 J7
 J3	 J8	 J10
 J1	 J4	 J11
 J14	 J6	 J5
		 J2



# ORIGINAL SpaGlo<sup>®</sup> MODULE REMOVAL

## STEP 1

### SpaGlo<sup>®</sup> MODULE REMOVAL

#### DANGER



Disconnect Power to spa before opening the Control Box to prevent possible electrocution.

1. Turn the power off to the spa.
2. Remove the equipment compartment door.
3. Access the control box by removing control box cover.
4. Cut the zip-ties that holds the LED cables together.
5. Remove the screws that hold the unit to the



#### IMPORTANT

Make sure to label all connections with original SpaGlo port number (Figure 1.1).




Figure 1.1

equipment compartment wall.

6. Open SpaGlo module lid.
7. Disconnect and label all of the SpaGlo cable connections. See (Figure 2.3) for connections.

#### NOTE

Scrap original SpaGlo module connection cables for power(J12) and communication(J14). These cables will no longer be used in new SpaGlo eagle retrofit.

# SpaGlo® EAGLE RETROFIT CONTROLLER INSTALLATION

## STEP 1

### SpaGlo® EAGLE RETRO INSTALLATION

#### DANGER



Power to spa must remain off before opening the Control Box to prevent possible electrocution.

1. Access new SpaGlo controller by removing the cover screws.
2. Take all the previously-labeled cables and plug them into the new SpaGlo controller.
3. Using new cables provided in kit, connect

#### NOTE

Connection ports(J12) and (J14) on new SpaGlo controller will require new cables that are included with kit 78864.



Figure 2.1

cables to the Eagle control box and SpaGlo module:

- J12 (module) connects to Zone 4(Eagle).
  - J14 (module) connects to Zone 1(Eagle).
4. Once you have connected all cables, tie all the cables together with zip-ties.
  5. Route all of the wires in the SpaGlo controller out to the side of the box.
  6. Replace the cover on the control box.
  7. Replace the cover on the SpaGlo controller.
  8. Secure SpaGlo controller with screws inside equipment compartment.




Figure 2.2

COLOR	USE	PORT	NOTES:
NA	EAGLE CONTROL BOX ZONE 4	J12	
NA	EAGLE CONTROL BOX ZONE 1	J14	
RED	GROUP A: 3 DOWNLIGHTS	J2, J3, J4	
RED	GROUP B: 3 DOWNLIGHTS	J5, J7, J8	
GREEN	GROUP C: GRABRAIL	J9	
GREEN	GROUP C: WATERFALL	J10	In spas without a waterfall feature install adapter plug.
NA	GROUP D: FILTER/ON BOARD LIGHTS	J11	
NA	GROUP E: SPA LIGHT	J1, J13	

Figure 2.3



**WatkinsWellness®**

*Feel good. Live well.™*