



AA300 Induct Style Dehumidifier

with option for air & pool water heating

_calorex

A compact ducted dehumidifier for pools with simple ducting requirements.

AA300 SPECIFICATIONS

MODEL	AA300	AA300/L	AA300/WL
Operating conditions - ^o C	15-36	15-36	15-36
Dehumidification rate			
(30°C / 60% RH) - ltrs / hr	3.6	3.6	3.6
HEAT TO AIR	4.4	4.4	4.4
Via heat pump (mode B) - kW Via LPHW @ 80ºC - kW	4.4	4.4 7.3	4.4 7.3
Total (mode B) - kW		-	9.8
Heat to water - kW	-	-	18
BOILER CAPACITY			
Recommended boiler capacity - kW	-	7.3	25.3
Recommended flow rates - I/min	-	10	21
Pressure drop @ rated flow - m/hd	-	2.8	4.2
Max system working pressure - bar	-	6	6
ELECTRICAL			
Total power consumed			
(nominal - F & non F) - kW	2	2	2
Min supply capacity - Amps	13	13	13
Max supply fuse - 1ph N - F & non F - Amps	20	20	20
MAIN FAN			
Air flow (anenometer @ air on filter, wet evaporator) - m3/hr	1300+10%	1300+10%	1300+10%
Max external static pressure - Pa	110	110	110
Normal running current - Amps	1.5	1.5	1.5
Max running current - Amps	2.6	2.6	2.6
COMPRESSOR			
Nominal power consumed - kW	1.9	1.9	1.9
Normal running current - Amps	4.6	4.6	4.6
Max running costs - Amps	8.6	8.6	8.6
GENERAL DATA			
Gas charge (R407c) - kg	2.6	2.6	2.6
LPHW battery volume - litres	-	1.15	1.15
Noise level @ 1m - dBA	61	61	61
DIMENSIONS			
H x W x D - mm	850 x 730	850 x 730	850 x 730
	x 1025	x 1025	x 1025
Weight - kg	111	111	111

Features of the AA 300 VH


- 3.6l/hr at 30°C / 60% RH
- 0-1300 m³/hr variable speed fan with two external static pressure settings
- 12V remote control panel, 5m lead
- Fresh air introduction point
- Air filters and duct flanges
- Temperature setback control (LPHW version)
- Options: 20m control panel lead, Air LPHW, Air and water LPHW




Control panel kit can be mounted up to 20 metres away (additional cable required).



Air and water LPHW control panel





This literature is intended as a guide. The Company reserves the right to change the specifications without notice. 24.02.14



Certikin International Ltd www.certikin.co.uk

